

DAHI1050 (DH-VTO1210C-X)

Foyer Panel (IP)



Features

- 3-inch STN screen, vivid pictures are on show
- Stainless steel panel, mechanical buttons
- Adopt TCP/IP network host, supports SNMP network protocol
- Network security technology provides stable and safe operating environment
- Supports night vision, voice indication
- Surface mount & Flush mount available
- Supports card and password to open the door
- IP54

DAHI1050 (DH-VTO1210C-X)

Specifications

Model		DH-VTO1210C-X
System	Main Processor	Embedded micro processor
	Operation System	Embedded LINUX OS
Video	Video Compression Standard	H.264
	Input/Approaching Induction	1.3 megapixel CMOS camera
	Black Light	Supported
	Auto Light Compensation	Supported
Audio	Audio Input	Microphone
	Audio Output	Built-in speaker
	Bidirectional Talk	Support dual-way bidirectional talk
Display	LCD Dimensions	3-inch STN screen
	Resolution	128*64
Operation Mode	Input	Mechanical buttons
	Card	Built-in IC card induction reader
Approaching Induction	Body Approaching	IR, 1 meter
Alarm	Vandal proof	Supported
Access Control	No Output	Supported
	NC Output	Supported
	Door on/off Button	Supported
	Door Status Detect	Supported
Network	Ethernet	10M/100Mbps Self-adaptive
	Network Protocol	TCP/IP
Storage	Memory	128MB
Others	Power	DC 12V
	Power Consumption	Standby ≤1W, work ≤10W
	Working Environments	-40°C – +60°C
		10% – 95%RH
	Water Proof	IP54
	Dimensions	406.0mm*143.0mm*42mm (L*W*T)
Weight	1.6Kg	

*Design and specifications are subject to change without notice.