

# DHU13570 (NKB3000)

## HD Network Control Keyboard



**DH-NKB3000:** Programmable 4D-switch desktop HD Network keyboard

### Features

- > Keyboard to Control:
  - DAHUA Standalone DVR
  - DAHUA (Network) High Speed Dome
  - DAHUA High Speed Dome
  - Central Management Platform
  - Network Video Server
- > RS232, RS485 & Network Connections
- > Four Dimensional Joystick Control of PTZ Functions
- > Supports full HD 1080p live view; Support HDMI & VGA sync output
- > Supports snapshot and recording to U-disk
- > Supports Video-Wall display
- > Supports external Wi-Fi (Optional)
- > Supports bidirectional talk
- > Preset Position, Auto Scan, Auto Pan, Auto Tour & Pattern Control
- > Auxiliary Functions, OSD and operation guides.

# DHU13570 (NKB3000)

## Technical Specifications

|                      |                |   |   |
|----------------------|----------------|---|---|
| <b>Model</b>         |                | <b>DH-NKB3000</b>                                   |   |
| <b>System</b>        |                |   |   |
| Main Processor       |                | Industrial embedded microprocessor                  |   |
| Operation System     |                | Embedded LINUX                                      |   |
| <b>Audio</b>         |                |   |   |
| Compression          |                | G.711A  |   |
| Output               |                | 1ch output  |   |
| Bidirectional Talk   |                | 1ch input and 1ch output                            |   |
| <b>Display</b>       |                |   |   |
| Display split        |                | 1/4/8/9/16  |   |
| Resolution           |                | 1080P/720P/D1/HD1/BCIF/CIF/QCIF                     |   |
| Screen               |                | 10.2" touch screen LCD (touch pen)                  |   |
| <b>General</b>       |                |   |   |
| Keyboard Panel       |                | Electromechanical                                   |   |
| Joystick             |                | 4-axis(zoom, focus, iris)                           |   |
| Control              | Output Control | Support video-wall display<br>HDMI/VGA output       |   |
|                      | Control Mode   | Direct Mode   | Interface: 1 RS232/ 2 RS485<br>DVR Protocol: DH1/DH2 Dome Protocol:<br>DH-SD/PELCO-D/PELCO-P/PELCO-D1/PELCO-P1 and etc. |
|                      |                | Network Mode  | Interface: RJ45(1 RJ-45 port (10/100/1000M)) / Wi-Fi<br>DVR/Network Dome:<br>IP Address/Port/Protocol                   |
| Max Remote Users     |                | 20 (each can manage up to 256 unit devices)         |   |
| USB Interface        |                | 2 ports, for mouse control & backup                 |   |
| <b>Environmental</b> |                |   |   |
| Power Supply         |                | DC12V   |   |
| Power Consumption    |                | 5W  |   |
| Working Temperature  |                | -10°C ~ +55°C                                       |   |
| Working Humidity     |                | 10%~90%   |   |
| Atmosphere Pressure  |                | 86kpa~106kpa  |   |
| Dimension            |                | 480mmx240mmx87mm (WxDxH) (height: exclude joystick) |   |
| Weight               |                | 4.5KG   |   |

\*Design and specifications are subject to change without notice.

© 2012 Dahua Technology Co., Ltd.



**seadan**  
security & electronics



VIC Unit 7, 170 Forster Road, Mt Waverley VIC 3149  
NSW Unit 5, 142 James Ruse Drive, Parramatta NSW 2150  
QLD 15-19 Hudson Road, Albion QLD 4010  
WA Unit 4, 200 Balcatta Road, Balcatta WA 6021  
ACT Unit 2, 157-161 Gladstone Street, Fyshwick ACT 2609

You're in very secure company

1300 366 851 | [seadan@seadan.com.au](mailto:seadan@seadan.com.au)

20161018