



# High Quality Door Strikes



## DBS284 (fail secure) For timber or metal door frames

**Application:**  
Internal use (only)  
**Recommended Lock:**  
Key in knob or mortice locks  
**Voltage:**  
12 volt AC or DC  
**Current consumption:**  
160ma @ 12 vac 160ma @ 12 vdc  
**Backset:**  
20mm  
**Face plate dimensions:**  
148mm X 28mm  
(not including 11mm for the extension lip)




## DBS283 (fail secure) For timber aluminum or steel door frames

**Application:**  
Internal use (only)  
**Recommended Lock:**  
Lockwood 3580/3570 or similar  
**Voltage:**  
12 volt AC or DC  
**Current consumption:**  
160ma @ 12 vac 160ma @ 12 vdc  
**Backset:**  
20mm  
**Face plate dimensions:**  
178mm X 33mm—now available with counter sunk holes  
(not including 11mm for the extension lip)



## DBS281 (fail secure) For timber door frame

**Application:**  
Internal use (only)  
**Recommended Lock:**  
Mortice or key in knob  
**Voltage:**  
12 volt AC or DC  
**Current consumption:**  
160ma @ 12 vac 160ma @ 12 vdc  
**Backset:** 20mm  
**Face plate dimensions:**  
146mm X 25mm  
**Accessories:**  
Stainless steel surface mount housing 7301200 or L- shape 14kis



## DBS282 (fail safe) For 12mm glass panels

**Application:**  
Internal use (only)  
**Glass size:**  
12mm (allow 3mm gap)  
**Voltage:**  
12 volt DC  
**Current consumption:**  
160ma @ 12 vdc  
**Backset:**  
20mm  
**Face plate dimensions:**  
148mm X 28mm



## 7301200 Housing (left)

**Construction:**  
stainless steel  
**Recommended strike:**  
EDH DBS281  
**Dimension:**  
150mm x 44mm x 28mm



## 12 KIS Housing

**Construction:**  
stainless steel  
**Recommended strike:**  
EDH DBS281  
**Dimension:**  
140mm x 44mm x 28mm  
(plus 23mm fixing plate)

